

Thermal Transfer Ribbon Resin Datasheet

HL35 Resin Ribbon

- A highly durable resin ribbon suitable for flat head printers
- Designed for printing onto care labels and standard label media
- Excellent wash & dry clean resistance
- · Resists ironing and steam pressing
- **Resists Petrol**
- **UL Listed**
- Oeko-tex Class 1 approved product

Technical Specification

Ink Composition Resin

Colours Black

Film Thickness $4.5 \mu + 0.5 \mu$


Total Thickness $7.5 \mu + 1.0 \mu$

Ink Melting Point 90°C

Max Print Speed 100mm/ Sec

RESIN FLATHEAD

Print Performance



Applications



TEXTILES



AUTOMOTIVE



CHEMICAL



PETROL



FOOD







Approvals · Compliance





REACH- SVHC FREE FDA Listed

UL Listed

FOOD CONTACT EN71/3 TOY SAFE



AVIATION



ISO 9015:2008







ROHS

ISO 14001:2015

HALOGEN FREE BS EN ISO 105 C06 BS EN ISO 105 D01

OEKO-TEX 1

Recommended Stock

Textile Care Label Media

Synthetic Media (PP, PE, PET, PVC)

DYNIC (UK) LTD **Trident Business Park** CF24 5EP **United Kingdom**

Tel +44 (0) 2920 483 973 Fax +44 (0) 2920 486 706

Storage

Temperature 5°C to 35°C **Relative Humidity** 30% to 80% Shelf life 12 months

Keep away from direct sunlight MSDS available upon request